



© NXP SEMICONDUCTORS N.V. ALL RIGHTS RESERVED	<b>MECHANICAL OUTLINE</b>	PRINT VERSION NOT TO SCALE
TITLE:  <p style="text-align: center;">SOT 343R</p>	DOCUMENT NO: 98ASA10524D	REV: D
	STANDARD: NON-JEDEC	
	SOT1763-1	10 MAR 2016



NOTES:

1. DIMENSIONS ARE IN MILLIMETERS.
  2. INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994.
  3. DIMENSION AT DATUM A AND B DOES NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS.
  4. DIMENSION AT DATUM A AND B ARE DETERMINED AT THE OUTMOST EXTREMES OF THE PLASTIC BODY EXCLUSIVE OF MOLD FLASH, TIE BAR BURRS, GATE BURRS AND INTERLEAD FLASH, BUT INCLUDING ANY MISMATCH BETWEEN THE TOP AND BOTTOM OF PLASTIC BODY.
  5. TERMINAL NUMBERS ARE SHOWN FOR REFERENCE ONLY.
- △ 6. THIS DIMENSIONS APPLY TO THE FLAT SECTION OF THE LEAD BETWEEN 0.08mm AND 0.15mm FROM THE LEAD TIP.

© NXP SEMICONDUCTORS N.V. ALL RIGHTS RESERVED	<b>MECHANICAL OUTLINE</b>	PRINT VERSION NOT TO SCALE
TITLE:  SOT 343R	DOCUMENT NO: 98ASA10524D      REV: D	
	STANDARD: NON-JEDEC	
	SOT1763-1      10 MAR 2016	