



DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	27.43	28.45	1.080	1.120
B	18.80	19.30	0.740	0.760
C	16.00	16.51	0.630	0.650
D	0.41	0.51	0.016	0.020
E	4.06	4.57	0.160	0.180
F	1.22	1.63	0.048	0.064
G	2.54	BSC	0.100	BSC
J	0.36	0.41	0.014	0.016
K	5.59	6.10	0.220	0.240
N	1.78	2.03	0.070	0.080
P	3.81	4.06	0.150	0.160
Q	3.81	4.06	0.150	0.160
R	11.18	11.68	0.440	0.460
S	17.65	18.42	0.695	0.725
U	21.34	12.84	0.840	0.860
V	4.62	4.92	0.182	0.194

NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994
2. CONTROLLING DIMENSION: INCH.

STYLE 1:

- PIN 1. GROUND
- 2. V (+) OUTPUT
- 3. V SUPPLY
- 4. V (-) OUTPUT

© NXP SEMICONDUCTORS N.V.  
ALL RIGHTS RESERVED

MECHANICAL OUTLINE

PRINT VERSION NOT TO SCALE

TITLE:  
SENSORS GSX & ASX  
01ASB09025C, 98ASB09087B

DOCUMENT NO: 98ASB14915C REV: D

STANDARD: NON-JEDEC

SOT1757-1

18 JAN 2016