

**Table of Contents**

1	Title
2	Notes
3	Sensors

**Revisions**

Rev	Description	Date
X1	Original Release	04-09-15
A	Release	11-5-15

# BRKTSTBCDP5004

		<b>RF, Analog &amp; Sensor Group</b>	
		6501 William Cannon Drive West Austin, TX 78752-9299	
<small>This document contains information proprietary to Freescale Semiconductor and shall not be used for engineering design, procurement or manufacture in whole or in part without the express written permission of Freescale Semiconductor.</small>			
Designer: Frank L.		Drawing Title: <b>BRKTSTBCDP5004</b>	
Drawn by: Frank L.		Page Title: <b>CONTENT</b>	
Approved: Team	Size C	Document Number SCH-28987 PDF: SPF-28987	Rev A
Date: Thursday, November 05, 2015		Sheet	1 of 3

1. Unless Otherwise Specified:

All resistors are in ohms, most are 1%, 1/10 Watt. Otherwise are 5%, 1/8 Watt.

All capacitors are in uF, some are 10% or 20%

All voltages are DC

All polarized capacitors are tantalum

2. Interrupted lines coded with the same letter or letter combinations are electrically connected.

3. Device type number is for reference only. The number varies with the manufacturer.

4. Special signal usage:

\_B Denotes - Active-Low Signal

<> or [] Denotes - Vectored Signals

5. Interpret diagram in accordance with American National Standards Institute specifications, current revision, with the exception of logic block symbology.



ICAP Classification: FCP: FUC: X PUB:		
Drawing Title: <b>BRKTSTBCDP5004</b>		
Page Title: <b>NOTES</b>		
Size C	Document Number SCH-28967 PDF: SPF-28967	Rev A
Date: Thursday, November 05, 2015	Sheet 2 of 3	

