


Table of Contents

1	Title
2	Notes
3	Sensors

BRKT-STBC-SA9500

		RF, Analog & Sensor Group 6501 William Cannon Drive West Austin, TX 78752-8089	
<small>This document contains information proprietary to Freescale Semiconductor and shall not be used for engineering design, procurement or manufacture in whole or in part without the express written permission of Freescale Semiconductor.</small>			
Designer: Krithi S		ICAP Classification: FCP: FUK2: X PUBI:	
Drawn by: Krithi S		BRKT-STBC-SA9500	
CONTENT			
Approved: Team	Size C	Document Number SCH-28966 PDF: SPF-28966	Rev A1
Date: Sunday, October 11, 2015		Sheet 1 of 3	

1. Unless Otherwise Specified:

All resistors are in ohms, 5%, 1/8 Watt

All capacitors are in uF, 20%, 50V

All voltages are DC

All polarized capacitors are aluminum electrolytic

2. Interrupted lines coded with the same letter or letter combinations are electrically connected.

3. Device type number is for reference only. The number varies with the manufacturer.

4. Special signal usage:

_B Denotes - Active-Low Signal

<> or [] Denotes - Vectored Signals

5. Interpret diagram in accordance with American National Standards Institute specifications, current revision, with the exception of logic block symbology.



ICAP Classification:		FCP:	FIUC: X	PUBL:
Drawing Title:		BRKT-STBC-SA9500		
Page Title:		NOTES		
Size	Document Number	SCH-28966 PDF: SPF-28966		Rev
C				A1
Date:	Sunday, October 11, 2015	Sheet	2	of 3

EDGE OF BRKOUT BOARD

